



General Parameter	
Working Voltage	24V DC
Cuttable	14LEDs/section
LED Type	SMD 2835
LED Beam Angle	120
CRI	95+
R9	90+
FPC Substrate Color	White
FPC Width	12mm
FPC Thickness	4OZ
Working Temperature	0°C–40°C
Storage Temperature	-20°C–70°C
IP Rating	IP54 (Top Brand Silicone as conformal coating)
Lifespan	50,000h
Standard Package	17ft/roll
Dimmable	Yes
Certificates	CE, RoHS, ETL

You can make any space remarkable with this Tunable white LED Strip, offering full adjustment of the white light color temperature from 2000K warm white to 4000K neutral white (or 6000K cool white upon request) and every color temperature between with a tunable white controller (sold separately). It uses alternating neutral (or cool) and warm white chips. Easily cut the strip into separate segments and install it with its peel-and-stick 3M adhesive backing. It's great for cabinets, under-cabinet lighting, coves, task lighting, bookshelves, or for other indoor or damp location applications.





## Electro-optical Characteristics

LEDs/ft	Wattage	CCT(K)	Luminous Flux
70LEDs	4.8W/ft	2000+4000	415lm/ft
		2700+6000	450lm/ft

## TM-30-15 Data

**2000+4000K** Rf: 91.9/Rg: 102.8




## SKU Builder Direction

X1 Product Name	X2 LED Type	X3 LED Color	X4 LEDs	X5 FPC Color	X6 FPC Width	X7 IP Rate	X8 Voltage	X9 CRI
Code	Code	Code	Code	Code	Code	Code	Code	Code
FR LED Strip light	2835 SMD2835	EW 2000+4000K	70 70LEDs/ft	WH White	12 12mm	OE IP54	24 24V DC	T CRI>95
		EC 2700+6000K						










Example:  $\frac{FR}{X1} \frac{2835}{X2} \frac{EW}{X3} \frac{70}{X4} \frac{WH}{X5} \frac{12}{X6} \frac{OE}{X7} \frac{24}{X8} \frac{T}{X9}$



## Mechanical Diagram



## Accessories

Picture	Part No.	Description
	SL-V-12XXXP SL-V-24XXXP	Plastic Power Supply,output: DC12V or 24V, Output Power Options:12W,24W,36W,48W,60W,72W,96W,120W.
	SL-V-12XXXM SL-V-24XXXM	Metal Power Supply,output: DC12V or 24V, Output Power Options: 25W,50W,60W,100W,145W,200W,250W,350W,400W,500W.
	SL-V-12XXX SL-V-24XXX	Waterproof Power Supply,output: DC12V or 24V, Output Power Options:15W,18W,30W,40W,60W,100W,150W,200W.
	PUT022	DC12-24V, 2.4G Color Temperature and Brightness Adjusting LED Touching Remote Control, 6A/circuit
	SL-CL-F4	JST Female 4pin Connector with 15cm wire
	SL-CL-M4	JST Male 4pin Connector with 15cm wire
	SL-XBB-4	4pin Connector for strips 10mm/12mm/15mm with 15cm wire.
	SL-XBB-4A	4pin Connector for strips 10mm/12mm/15mm with 15cm wire.
	SL-XBB-Ax4	4pin Connector for strips 10mm/12mm/15mm with 15cm wire.